

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	REVISED AS PER ECR-15-005925	21APR2015	RS	JL
	A1	REVISED AS PER ECR-15-011749	10AUG2015	RS	JL

1.0

"PE" CONTACT

2.8  
4X

PART NO.  
2213234-1

M1.5 HEX  
DRIVE

"PE" CONTACT

"PE" SYMBOL

1.0

"PE" CONTACT

5.2  
4X

PART NO.  
1-2213234-1

M1.5 HEX  
DRIVE

CONTACT  
(5X)

CONTACT  
POSITIONER  
(1X)

NOTES:

1 MATERIALS:  
CONTACTS: COPPER ALLOY, TIN PLATE  
CONTACT POSITIONER: GLASS FILLED PBT,  
COLOR BLACK

2. MUST COMPLY WITH DIRECTIVE 2002/95/EC (ROHS)

3. CONTACTS (5X) ARE PRE-ASSEMBLED INTO CONTACT  
POSITIONER AS SHOWN.

4 CONTACTS ARE NOT INSTALLED  
INTO THE INDICATED CONTACT SLOTS

5 "PE" SYMBOL ALIGNS WITH "PE"  
CONTACT AS SHOWN

6. THIS PRODUCT HAS NOT COMPLETED  
VALIDATION TESTING

IEC (DEKRA)	1-2213234-1
UL	2213234-1
AGENCY APPROVALS	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
mm

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±0.2
2 PLC	±0.13
3 PLC	±-
4 PLC	±-
ANGLES	±-
FINISH	-

MATERIAL  
NOTE 1DWN  
J. SHAFFER 15JAN2014CHK  
M. LUKSIC 15JAN2014APVD  
M. LUKSIC 15JAN2014

PRODUCT SPEC

108-133014

APPLICATION SPEC

114-32111

WEIGHT  
-

Customer Drawing

NAME

SCREW TERMINAL PIN CONTACTS  
ASSY, 5POSN, NECTOR M-LINE SEALED

SIZE

A3

CAGE CODE

-

DRAWING NO

C-2213234

RESTRICTED TO

-

SCALE  
1:1SHEET  
1 OF 1REV  
A1

TE Connectivity

1470-19 (3/13)