



Click [here](#) for the 3D model.

| Dimensions | |
|------------|-----------------|
| L | 24mm MAX |
| H | 16.5mm MAX |
| T | 11.3mm MAX |
| S | 20.3mm +/-0.4mm |
| LL | 30mm +5mm |
| F | 0.8mm +/-0.05mm |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 150 |

| General Information | |
|--------------------------|---|
| Series | PMR209 |
| Dielectric | Metallized Paper |
| Style | Radial |
| Features | RC Unit approved |
| RoHS | Yes |
| Lead | Wire Leads |
| Qualifications | ENEC, UL, cUL |
| AEC-Q200 | No |
| Construction | Molded |
| Typical Component Weight | 6.3 g |
| Miscellaneous | Resistor= 22 Ohms. |
| Notes | Not For New Design, Please Use The New P409 Series @ 275 VAC. |

| Specifications | |
|-----------------------|-----------|
| Capacitance | 0.22 uF |
| Capacitance Tolerance | 20% |
| Voltage AC | 250 VAC |
| Voltage DC | 630 VDC |
| Temperature Range | -40/+85°C |
| Rated Temperature | 85°C |
| Insulation Resistance | 3 GOhms |
| Safety Class | X2 |