

CATALOG NUMBER

UTB60DP



CERTIFICATIONS



FEATURES

- Compact design universal transient barrier provides protection of low-voltage circuits and transducers
- Separate plug and base design allows hot swappable module replacement
- Multi-stage protection and fine over-voltage protection helps ensure lowest residual surge voltages reach sensitive equipment
- Common-mode and differential-mode protection protects against both possible surge conditions
- Surge rating to 20 kA 8/20 μ s is ideal for exposed wiring
- Allows for protection of 25 analog signals or 50 digital signals per linear foot (0,3 m) of DIN rail space

PRODUCT ATTRIBUTES

- Nominal System Voltage (U_n): 21 - 42 VAC; 30 - 60 VDC
- Max Continuous Operating Voltage (U_c): 45 VAC; 64 VDC
- Rated Load Current (I_L): 800 mA
- Frequency: 3 MHz
- Loop Resistance: 0.6 Ω
- Max Discharge Current (I_{max}), L+L-PE: 20 kA 8/20 μ s
- Protection Modes: Common; Differential
- Technology: Gas Discharge Tube (GDT); Metal Oxide Varistor (MOV); Silicon Avalanche Diode (SAD)
- Voltage Protection Level (U_p), L-L: 85 V @ 3 kA V
- Connection, Stranded: #18 min

Mounting: 35 mm top hat DIN rail

Temperature: -4 to 149 °F

Enclosure Material: UL® 94V-0 Thermoplastic

Enclosure Rating: IP 20; NEMA®-1

Depth (D): 3.35"

Height (H): 3.54"

Width (W): 0.47"


Unit Weight: 0.2 lb

Certification Details: UL® 497B

Complies With: ANSI®/IEEE® C62.41.2-2002 Cat A, Cat B, Cat C

Replacement Module: UTB60DPM

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com **CADDY ERICO HOFFMAN RAYCHEM SCHROFF**
TRACER