



Part Number : 1301530110

**Product Description** : Super-Safeway In-Line Industrial GFCI, IP69K, Portable, Single Phase, Manual Reset, Flying Leads, 20A, 120V, 0.61m (2.0') Cord Length

Series Number : 130153

Status : Active

Product Category : Power Distribution

Engineering Number : 20051-0M

---

## Documents & Resources

### Drawings

Drawing 1301530110\_sd.pdf

---

## Product Environment Compliance

### Compliance

|                    |   |
|--------------------|---|
| GADSL/IMDS         | Not Relevant                                  |
| China RoHS         | Not Reviewed per SJ/T 11365-2006              |
| EU ELV             | Not Relevant                                  |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21               |
| REACH SVHC         | Not Reviewed per D(2023)8585-DC (23 Jan 2024) |
| EU RoHS            | Not Reviewed per EU 2015/863                  |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### EU RoHS Certificate of Compliance

---

## Part Details

### General

|                    |   |
|--------------------|---|
| Status             | Active  |
| Category           | Power Distribution  |
| Series             | 130153  |
| Description        | Super-Safeway In-Line Industrial GFCI, IP69K, Portable, Single Phase, Manual Reset, Flying Leads, 20A, 120V, 0.61m (2.0') Cord Length |
| Enclosure Rating   | NEMA 4X   |
| NEMA Configuration | N/A   |
| Product Family     | Ground Fault Circuit Interrupter (GFCI) Products  |
| Product Name       | Super-Safeway   |
| Type               | GFCI Industrial Duty, Single Phase  |
| UPC                | 78678889742   |

#### Agency

|    |        |
|----|--------|
| UL | E66308 |
|----|--------|

#### Electrical

|                               |             |
|-------------------------------|-------------|
| Current - Maximum per Contact | 20.0A       |
| GFCI                          | Yes-In-line |
| GFCI Reset                    | Manual      |
| Ground Continuity Monitor     | No          |
| Open Neutral Relay            | Yes         |
| Voltage - Maximum             | 120V        |

#### Physical

|                     |                         |
|---------------------|-------------------------|
| Cord Diameter       | 10.67mm (.420")         |
| Cord Grip Body Size | Internal Double C-Clamp |
| Cord Length         | 0.61m (2.0')            |
| Cord Type           | 12/3 SJEOW              |
| Feed-Thru           | Yes                     |
| Flip Lid            | No                      |
| Material - Housing  | Nylon                   |
| Mounting Style      | Portable                |
| Net Weight          | 680.388/g               |

|                       |     |
|-----------------------|-----|
| Number of Receptacles | 0   |
| Packaging Type        | Bag |
| Receptacle Type       | N/A |

---

This document was generated on Apr 11, 2024