

Part Number : 1731130100

Series Number : 173113 Product Category : D-Sub Connectors

#### **Documents & Resources**

Drawings

Drawing 1731130100\_sd.pdf

### Product Environment Compliance

#### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | ®   |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-<br>21            |
| REACH SVHC         | Not Contained per D(2023)3788-DC<br>(14 Jun 2023) |
| EU RoHS            | Compliant per EU 2015/863                         |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

## **Part Details**

General

Product Description : FCT High-Density D-Sub Crimp Housing, Female, 26 Circuits Status : Active Engineering Number : FL15-26S7

| Status         | Active   |
|----------------|--|
| Category       | D-Sub Connectors   |
| Series         | 173113   |
| Description    | FCT High-Density D-Sub Crimp<br>Housing, Female, 26 Circuits |
| IP Rating      | IP20   |
| Product Family | FCT D-Sub Connectors   |
| Product Name   | FCT Products   |
| Туре           | High Density   |
| UPC            | 889056614573   |

# Electrical

| Shielded Yes |
|--------------|
|--------------|

# Physical

| Circuits (Loaded)              | 0        |
|--------------------------------|----------|
| Circuits (maximum)             | 26       |
| Color - Resin                  | Black    |
| Durability (mating cycles max) | 500      |
| Gender                         | Female   |
| Material - Resin               | PBT      |
| Material - Shell               | Steel    |
| Net Weight                     | 5.900/g  |
| Number of Rows                 | 3        |
| Orientation                    | Straight |
| Packaging Type                 | Carton   |
| Panel Mount                    | Rear     |
| Panel Mount Method             | Flange   |
| PCB Locator                    | No       |
| PCB Retention                  | None     |
| Pitch - Mating Interface       | 1.98mm   |
| Pitch - Termination Interface  | 1.98mm   |
| Plating - Shell                | Tin      |
| Polarized to Mating Part       | Yes      |
| Ports                          | 1        |

| Temperature Range - Operating | -55° to +105°C |
|-------------------------------|----------------|
| Termination Style             | Crimp          |
| Waterproof / Dustproof        | No             |
| Waterproof / Dustproof Type   | IP20           |
| Wire Size (AWG)               | 22, 24, 26, 28 |

# Mates With / Use With

# Mates with Part(s)

| Description | Part Number  |
|-------------|--|
| Mates With  | FCT High-Density D-Sub, Size 2, 26<br>Position, Plug |

### Use with Part(s)

| Description                       | Part Number                 |
|-----------------------------------|-----------------------------|
| FCT Machined Contact, Female,     | /content/molex/molex-dot-   |
| Crimp, 0.20µm Gold Plating, Split | com/us/en/products/product- |
| Tine, 22-28 AWG, 500 Pieces       | page.html/1731120226.html   |
| FCT Machined Contact, Female,     | /content/molex/molex-dot-   |
| Crimp, 0.80µm Gold Plating, Split | com/us/en/products/product- |
| Tine, 22-28 AWG, 500 Pieces       | page.html/1731120227.html   |
| FCT Machined Contact, Female,     | /content/molex/molex-dot-   |
| Crimp, 1.30μm Gold Plating, Split | com/us/en/products/product- |
| Tine, 22-28 AWG, 500 Pieces       | page.html/1731120228.html   |

This document was generated on Apr 12, 2024