




USSK20-12MM-7/16"-F

Ruland USSK20-12MM-7/16"-F, 12mm x 7/16" Single Universal Joint, Friction Bearing, Steel, Set Screw With Keyway, 1.245" (31.6mm) OD, 3.750" (95.3mm) Length





Description

Ruland USSK20-12MM-7/16"-F is a single cardan friction bearing universal joint with 12mm x 0.4375" bores, 4mm x 3/32" keyways, 1.245" (31.6mm) OD, 3.750" (95.3mm) length, and 5/16-18 set screws. It is ideal for applications with space constraints and has higher torque capacity than equivalently sized double universal joints. This plain bearing universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 45° when compared to commodity style single universal joints. USSK20-12MM-7/16"-F is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT20/32-NI-KIT to protect the joint from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This single cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

12 mm	Small Bore (B2)	0.4375 in
4 mm	Keyway (K2)	3/32 in
1.250 in (31.8 mm)	B2 Max Shaft Penetration	1.250 in (31.8 mm)
1.245 in (31.6 mm)	Bore Tolerance	+0.0010 in / -0.0000 in (+0.025 mm / -0.000 mm)
3.750 in (95.3 mm)	Yoke Length (LY)	1.875 in (47.6 mm)
1.250 in (31.8 mm)	Broached Set Screw	5/16-18
Black Oxide	Peak Torque	5200 in-lb (587.5 Nm)
1,040 in-lb (117.5 Nm)	Max Operating Angle	45°
Alloy Steel	Manufacturer	Belden Universal
USA	Weight (lbs)	0.861000
LUBRIPLATE No. 1200-2	Matching Boot Cover	UBOOT20/32-NI-KIT
63452937099	Tariff Code	8483.60.4000
25173810		
Performance ratings are for guidance only. The user must determine suitability for a particular application.		
⚠WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov .		
	4 mm 1.250 in (31.8 mm) 1.245 in (31.6 mm) 3.750 in (95.3 mm) 1.250 in (31.8 mm) Black Oxide 1,040 in-lb (117.5 Nm) Alloy Steel USA LUBRIPLATE No. 1200-2 63452937099 25173810 Performance ratings are for guida MARNING This product can e California to cause cancer and bin	4 mm Keyway (K2) 1.250 in (31.8 mm) B2 Max Shaft Penetration 1.245 in (31.6 mm) Bore Tolerance 3.750 in (95.3 mm) Yoke Length (LY) 1.250 in (31.8 mm) Broached Set Screw Black Oxide Peak Torque 1,040 in-lb (117.5 Nm) Max Operating Angle Alloy Steel Weight (lbs) LUBRIPLATE No. 1200-2 Matching Boot Cover 63452937099 Tariff Code 25173810 Performance ratings are for guidance only. The user must determine was a cause cancer and birth defects or other reproductive has